

MATERIAL SAFETY DATA SHEET

Effective and Print Date: 7/1/11 MSDS #1522011A Page #1

SECTION I - PRODUCT AND COMPANY IDENTIFICATION

Product Code: 152 PL Part A (Resin)
Product Name: NSP 152 PL Industrial/Commercial Floor Coating
Product Class: Modified Epoxy Resin
CAS Number: None Assigned

NSP Specialty Products, P. O. Box 4690, Pinehurst, NC 28374-4690 -ChemTel 24hr US Emergency Number:
800-255-3924/Worldwide Emergency Number + 1 813-248-0585

SECTION II - INFORMATION ON INGREDIENTS

Ingredients CAS# Exposure Limits

Modified Epoxy Resin	Proprietary	None Assigned
N-Butyl Glycidyl Ether	2426-08-6	ACGIH TVL 25 ppm
Titanium Dioxide	13463-67-7	OSHA PEL 15.0 mg/cu.m
Microcrystalline Silica,tripoli	1317-95-9	ACGIH TLV 0.1 mg/cu.m
Contains other ingredients and pigments which should be treated as nuisance dust - TLV - 10 mg/cu.m, 8 hr. TWA (total dust)		

SECTION III - HAZARDS IDENTIFICATION

*******EMERGENCY OVERVIEW*******

Viscous resinous material with mild, characteristic odor. Color indicated on label. Eye and skin irritant. May cause irritation and allergic skin reactions. Avoid contact with eyes, skin and clothing.

Potential Health Effects

EYE: Causes mild to moderate eye irritation.

SKIN: May cause irritation and allergic skin reactions.

INGESTION: Low acute oral toxicity.

INHALATION: May cause respiratory tract irritation.

CHRONIC (CANCER INFORMATION): Contains Microcrystalline Silica. Inhalation of silica dust (respirable) may cause delayed lung injury or disease. The International Agency for Research on Cancer (IARC) has evaluated that there is "sufficient evidence" that Microcrystalline Silica can cause cancer in laboratory animals and there is "limited evidence" with respect to humans. IARC Monograph: Level 2A Grouping. Take appropriate measures to avoid breathing spray during application or removal of cured product by use of NIOSH approved respirator.

MATERIAL SAFETY DATA SHEET

Effective and Print Date: 7/1/11 MSDS #1522011A Page #2
Product Code: 152 Part A (Resin)

SECTION IV - FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids apart to ensure rinsing of entire eye surface and lids with water.

SKIN: Promptly wipe clean with paper or cloths and wash with soap and water for at least 15 minutes. Remove, discard or decontaminate clothing prior to use.

INGESTION: If swallowed, give at least 3-4 glasses of water and seek medical attention. Do not give anything by mouth to an unconscious or convulsing person. Get medical attention and have physician determine whether vomiting or stomach evacuation is necessary. If mixed product (152 Part A and Part B) is swallowed, follow above steps and get immediate medical attention. No specific antidote.

INHALATION: If ill effects occur, remove to fresh air. Keep warm and quiet and get medical attention promptly.

SECTION V - FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

FLASH POINT: > 178 F Method: Seta Flash

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide and aldehydes.

EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical or water spray.

FIRE FIGHTING INSTRUCTIONS: Firefighters should wear goggles and self-contained breathing apparatus to avoid inhalation.

SECTION VI - ACCIDENTAL RELEASE MEASURES

SMALL SPILL:

Absorb spill with suitable absorbent material (dry sand, earth) and shovel into closed containers for proper disposal. Flush contaminated area with water.

LARGE SPILL:

Dike area and pump into closed containers. Prevent runoff from entering into storm sewers and ditches that could lead to natural waterways. Wear protective equipment during cleanup.

SECTION VII - HANDLING AND STORAGE

HANDLING:

This material may cause irritation. Do not get in eyes, on skin or clothing. Do not allow contaminated clothing to come in contact with skin. Avoid contact with vapors and fumes. Wear protective equipment.

STORAGE:

Store in closed containers in cool, dry, place. Avoid heat and warm storage areas.

MATERIAL SAFETY DATA SHEET

Effective and Print Date: 7/1/11
Product Code: 152 Part A (Resin)

MSDS #1522011A Page #3

SECTION VIII - EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING CONTROLS:

Control airborne concentrations below the exposure limits. Use only with adequate ventilation. Local exhaust and general ventilation is recommended.

RESPIRATORY PROTECTION:

NIOSH approved respirator suitable for organic vapors if TLV is exceeded.

SKIN PROTECTION:

Chemical-resistant plastic or rubber gloves. Wear protective equipment as required to prevent wetting the skin or clothing.

EYE PROTECTION:

Chemical splash goggles.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: > 327 F

VAPOR DENSITY: Not applicable

% VOLATILES: Negligible

SOLUBILITY IN WATER: Insoluble

SPECIFIC GRAVITY: 1.52

ODOR: Faint aromatic odor

APPEARANCE: Resinous, viscous liquid. Color indicated on label.

SECTION X - STABILITY AND REACTIVITY

CHEMICAL STABILITY: (CONDITIONS TO AVOID)

Keep away from heat and warm storage. Stable.

INCOMPATIBILITY:

Strong oxidizers and epoxy hardeners under uncontrolled conditions.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide, carbon dioxide, aldehydes.

HAZARDOUS POLYMERIZATION:

Will not occur in uncatalyzed state.

SECTION XI - TOXICOLOGICAL INFORMATION

Low acute oral toxicity: LD50 Rat > 2050 mg/kg

SECTION XII - ECOLOGICAL INFORMATION

None available

SECTION XIII - DISPOSAL CONSIDERATIONS

Care should be taken to ensure that the material or its containers are disposed of in an approved facility in accordance with current federal, state and local regulations.

MATERIAL SAFETY DATA SHEET

Effective and Print Date: 7/1/2011 MSDS #1522011A Page #4
Product Code: 152 Part A (Resin)

SECTION XIV - TRANSPORT INFORMATION

Not regulated by DOT

SECTION XV - REGULATORY INFORMATION

OSHA:

Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA:

Does not contain any components with reportable quantities.

SARA SECTION 313 LISTED INGREDIENTS:

This product does not contain a substance that is subject to the reporting requirements of 40 CFR 372.

SECTION XVI - OTHER INFORMATION

This information herein is given in good faith and is accurate to the best of NSP Specialty Products knowledge based on published MSDS from manufacturers, however no warranty, express or implied, is made as to the accuracy or completeness of these data and recommendations.

MATERIAL SAFETY DATA SHEET

Effective and Print Date: 7/1/11 MSDS #1522011B Page #1

SECTION I - PRODUCT AND COMPANY IDENTIFICATION

Product Code: 152 PL Part B (Hardener)
Product Name: NSP 152 PL Industrial/Commercial Floor Coating
Product Class: Modified Epoxy Hardener
CAS Number: None Assigned

NSP Specialty Products, P. O. Box 4690. Pinehurst, NC 28374 ChemTel 24hr US Emergency Number: 800-255-3924/Worldwide Emergency Number + 1 813-248-0585

SECTION II - INFORMATION ON INGREDIENTS

Ingredients	CAS#	Exposure Limits
Amine Compound	Proprietary	None Assigned
Benzyl Alcohol	100-51-6	None Assigned
Benzenedimethanamine	1477-55-0	STEL 0.1 mg/m3

SECTION III - HAZARDS IDENTIFICATION

*******EMERGENCY OVERVIEW*******

Slightly viscous amber liquid with mild characteristic amine odor. Causes severe eye irritation. Causes skin irritation. May cause allergic skin reaction and sensitization. Avoid contact with eyes, skin or clothing. Avoid breathing mist or spray. Harmful if swallowed.

Potential Health Effects

Primary Route of Entry: Dermal

EYE: Causes severe eye irritation.

SKIN: Causes moderate to severe skin irritation. May cause allergic skin reaction and sensitization.

INGESTION: Substance is harmful if swallowed.

INHALATION: Prolonged or repeated inhalation may cause lung damage or respiratory irritation. Avoid breathing mist or spray.

CHRONIC (CANCER INFORMATION):

None known.

MATERIAL SAFETY DATA SHEET

Effective and Print Date: 7/1/11 MSDS #1522011B Page #2
Product Code: 152 Part B (Hardener)

SECTION IV - FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids apart to ensure rinsing of the entire eye surface and lids with water. If physician is not available, continue flushing for an additional 15 minutes. Get immediate medical attention.

SKIN: Immediately remove contaminated clothing and shoes. Wash affected areas with mild soap and water for at least 15 minutes. Get medical attention if necessary. Discard or decontaminate clothing prior to use.

INGESTION: If 152 Part B is swallowed, immediately give at least 3 - 4 glasses of water, but do not induce vomiting. If vomiting occurs, give fluids again. Do not give anything by mouth to an unconscious or convulsing person. Get immediate medical attention. If mixed product (152 Part A and Part B) is swallowed, follow above steps and get immediate medical attention.

INHALATION: If ill effects occur, remove to fresh air. If breathing is difficult, get immediate medical attention.

SECTION V - FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

FLASH POINT: > 243 Deg. F (117 Deg. C) Method: CC

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, aldehydes, nitrogen oxides,

EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical or water spray.

FIRE FIGHTING INSTRUCTIONS: Firefighters should wear goggles and self-contained breathing apparatus to avoid inhalation of hazardous combustion products.

SECTION VI - ACCIDENTAL RELEASE MEASURES

SMALL SPILL:

Avoid personal contact. Absorb spill with suitable absorbent material (dry sand, earth) and shovel into closed containers. Flush contaminated areas with water.

LARGE SPILL:

Ventilate area. Avoid personal contact. Dike area and pump into closed containers. Prevent runoff from entering into storm sewers and ditches that could lead to natural waterways. Wear protective equipment during cleanup.

MATERIAL SAFETY DATA SHEET

Effective and Print Date: 7/1/11 MSDS #1522011B Page #3
Product Code: 152 Part B (Hardener)

SECTION VII - HANDLING AND STORAGE

HANDLING:

Avoid all personal contact. Do not get in eyes, on skin or clothing. Do not allow contaminated clothing to come in contact with skin. Avoid contact with vapors and fumes. Wear protective equipment and wash thoroughly with mild soap and water after handling.

STORAGE:

Store in tightly closed containers in cool dry area to prevent moisture absorption and carbon dioxide contamination.

SECTION VIII - EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING CONTROLS:

Control airborne concentrations below the exposure limits. Use only with adequate ventilation. Local exhaust and general ventilation is recommended.

RESPIRATORY PROTECTION:

NIOSH approved respirator suitable for organic vapors if TLV is exceeded.

SKIN PROTECTION:

Chemical-resistant plastic or rubber gloves. Wear protective equipment as required to prevent wetting the skin or clothing.

EYE PROTECTION:

Chemical splash goggles or full face shield is recommended.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 347 F – (175 C)

% VOLATILES: NIL

SOLUBILITY IN WATER: Partly Soluble

ODOR: Amine

APPEARANCE: Yellow Liquid

VAPOR PRESSURE:: <2 Pa @ 68 F

DENSITY: 1.05 g/cm³ @ 77 F

SECTION X - STABILITY AND REACTIVITY

CHEMICAL STABILITY: (CONDITIONS TO AVOID)

Stable.

INCOMPATIBILITY:

Strong oxidizers, acids and epoxy resins under uncontrolled conditions.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide, carbon dioxide, aldehydes, nitrogen oxides.

HAZARDOUS POLYMERIZATION:

Will not occur.

MATERIAL SAFETY DATA SHEET

Effective and Print Date: 7/1/11 MSDS #1522011B Page #4
Product Code: 152 Part B (Hardener)

SECTION XI - TOXICOLOGICAL INFORMATION

Acute Oral Effects (LD50): Rat > 930 mg/kg

SECTION XII - ECOLOGICAL INFORMATION

None available.

SECTION XIII - DISPOSAL CONSIDERATIONS

Care should be taken to ensure that the material or its containers are disposed of in an approved facility in accordance with current federal, state and local regulations.

SECTION XIV - TRANSPORT INFORMATION

Not regulated by DOT

SECTION XV - REGULATORY INFORMATION

OSHA:

Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

RCRA:

Not a hazardous waste under RCRA (40 CFR 261)

SARA SECTION 313 LISTED INGREDIENTS:

This product does not contain a substance that is subject to the reporting requirements of 40 CFR 372.

TSCA Section 8(b) Inventory Status:

Chemical components listed on TSCA Inventory

Canadian Inventory Status:

This product is not included on the DSL or the NDSL.

SECTION XVI - OTHER INFORMATION

This information herein is given in good faith and is accurate to the best of NSP Specialty Products knowledge based on published MSDS from manufacturers, however no warranty, express or implied, is made as to the accuracy or completeness of these data and recommendations.